

Certifications

Approved by ENEDIS

Section

MV Multifunction

Application

Field

Laboratory

**PRODUCT BENEFITS**

Quick assembly - disassembly of accessories
 For cylindrical and branch fittings and lugs
 Circular abrasion of the sheath for a good seal

TOOL CAPACITY

Diameter 16 - 60 mm
 0,630 - 2,362 inch

Abrasion length 50 mm / 1,968 in

TOOL DIMENSIONS

Length 255 mm

Width 85 mm

Height 90 mm

Weight without box 0,84 Kg

Packaging Box

ALROC SAS

Z.I. de la Fonderie - 72160 TUFFE
 FRANCE

Phone: +33 2 43 71 11 80

Fax number : +33 2 43 71 16 51

www.alroc.fr

Tool for holding self-tightening, abrasion and re-tightening fittings

TO DO WHAT

The ROTO-TMG PACK consists of :

The ROTO-TMG tool for holding self-tightening lugs and fittings

The K7/GRATT accessory for the abrasion of the outer sheath

The GFE-TMG accessory for tightening the sheath on the pin plate

**Spare part**

LRTT - Spare blade sheath abrading (order by 2)

Associated tool

ALROC-FENTE - Tool to perform slits on cable's outer sheath

LIGAREX - Clamping tool with return spring for straps

BRMRD1E - Tool to remove insulation

C-RTT - Tool to replace blade for abrasion

MV cables Tools

PACK ROTO-TMG



Part Number	Diameter	Tool capacity	Dimensions			Packaging
		Abrasion length	Length	Width	Height	
PACK ROTO-TMG	16 - 60 mm 0,630 - 2,362 in	50 mm / 1,968 in	255 mm 10,039 in	85 mm 3,346 in	90 mm 3,543 in	box