

**Certifications**

Approved by ENEDIS

Section

MV Sets

ApplicationField
Laboratory**PRODUCT BENEFITS**New generation of Tools
Spare blades included**TOOL CAPACITY**

Diameter	16 - 58 mm 0,630 - 2,283 inch
Section according to voltage rating	50 - 630mm ²
Chamfer on peelable semi-conductor	Yes
Chamfer on bonded semi-conductor	Yes

TOOL DIMENSIONS

Length	575 mm
Width	470 mm
Height	145 mm
Weight without box	10 Kg
Packaging	Case

ALROC SASZ.I. de la Fonderie - 72160 TUFFE
FRANCE

Phone: +33 2 43 71 11 80

Fax number : +33 2 43 71 16 51

www.alroc.fr

Full kit for distribution underground cable 50 mm² up to 630 mm²**TO DO WHAT**

Tools included in the kit CNPT/630-2016 enable the user to splice each layer of distribution underground cable ranging from 50 mm² up to 630 mm² in 12/20 kV, prior to junctions or terminations installation.

For any other voltage rating, please check the outer diameter capacity of each tools included in the kit

**Associated tool**

SRC-D - Scoring stylus for peelable semiconductor with chamfer on the transition
CKM-HTA-630-NG - Case for self service kit for MV 630 NG case
AGPB3 - Pliers for lead sheath 26 - 52 mm / 1,024 - 2,047 in

Case

ROTO-TMG - Connector holder for bolted and clamping connections
K7/GRATT - Cartidge dedicated to sheath abrading, to be mounted on tool ROTO-TMG
MF2/60 - Multifonction tool for outer sheath and insulation
MF1+/60 - Tool for bonded semiconductor and peelable with stylus
ALROC-FENTE - Tool to perform slits on cable's outer sheath
EV/NPT - Tool to spread PE outer sheath with aluminium screen
GFE-TMG - Roller block for ROTO-TMG to tighten the outer sheath over screen connection
LIGAREX - Clamping tool with return spring for straps
GRI - Scraper for residues of bonded semiconductor
SCH - Chamfering stylus for insulation
LMF2 - Qty 2 - 2 spare blades for primary insulation
LASCR1 - Qty 2 - 2 spare blades for bonded semiconductor
LS-CD - Qty 2 - 2 Spare blades for semiconductor scoring with chamfer
LSCH - Qty 2 - 2 spare blades to chamfer insulation
LFE-V - Qty 2 - 2 spare blades split outer sheath + Screw

MV cables Tools

CNPT/630-2016



Part Number	Diameter	Tool capacity			Dimensions			Packaging
		Section according to voltage rating	Chamfer on peelable semi-conductor	Chamfer on bonded semi-conductor	Length	Width	Height	
CNPT/630-2016	16 - 58 mm 0,630 - 2,283 in	50 - 630mm ²	Yes	Yes	575 mm 22,638 in	470 mm 18,504 in	145 mm 5,709 in	case