

**Section**

HV Accessories

**Application**

Field

Laboratory

**PRODUCT BENEFITS**

Clean and precise stop making

**TOOL CAPACITY**

**Diameter** 35 - 90 mm  
1,378 - 3,543 inch

**Material** Aluminum with plastic inserts

**Rolling area** No

**TOOL DIMENSIONS**

**Length** 370 mm

**Width** 135 mm

**Height** 40 mm

**Weight without box** 1,2 Kg

**Packaging** None

**ALROC SAS**

Z.I. de la Fonderie - 72160 TUFFE  
FRANCE

Phone: +33 2 43 71 11 80

Fax number : +33 2 43 71 16 51

www.alroc.fr

## Multifunctional tool stop

**TO DO WHAT**

The BMF2 stop is fixed on the cable to stop the tools

It is used :

- On the outer sheath of the cable to stop the DMSR/40-90 tool
- On the semi-conductor to stop the CASR/35-75, LHS3 and LHM3R tools
- On the insulator to stop the LH3 tools

**Associated tool**

DMSR/40-90 - Reinforced stripping tool for hard outer sheath (PE, PEHD, Lead)

CASR/35-75 - Monofunction tool for bonded semiconductor, rounding up the cable

LHS3 - Monofunction tool for semiconductor

LHM3R - Monofunction tool for peelable semiconductor

LH3 - Monofunction tool for insulation

HV cables Tools

# BMF2



Part Number	Diameter	Tool capacity		Dimensions			Packaging
		Material	Rolling area	Length	Width	Height	
BMF2	35 - 90 mm 1,378 - 3,543 in	Aluminum with plastic inserts	No	370 mm 14,567 in	135 mm 5,315 in	40 mm 1,575 in	none