

MV cables Tools

MF3/45-C



Certifications

Approved by ENEDIS

Section

MV Multifunction

Application

Field
Laboratory



PRODUCT BENEFITS

3 in 1

Tuning of the pitch of the tool
Embedded wear pads to protect the tool from the contact with the outer sheath

TOOL CAPACITY

Diameter 16 - 45 mm
0,630 - 1,772 inch

Pelable semicon thickness capacity 0,4 - 1,5 mm / 0,016 - 0,040 in

Insulation thickness capacity 7 mm / 0,276 in

Stylus included SRC

TOOL DIMENSIONS

Length 303 mm

Width 95 mm

Height 165 mm

Weight without box 1,5 Kg

Packaging Box

ALROC SAS

Z.I. de la Fonderie - 72160 TUFFE
FRANCE

Phone: +33 2 43 71 11 80

Fax number : +33 2 43 71 16 51

www.alroc.fr

Multifunction tool for outer sheath, peelable semiconductor with chamfer and insulation

TO DO WHAT

The MF3/45-C tools enables the user to :

Remove the outer sheath (PE-PVC-PR) with a straight and neat cut

Score the peelable semiconductor with a chamfer on the edge of the semiconductor cutback (with the SRC scoring stylus delivered with the tool)

Set the length to be removed and remove the insulation with a straight and neat cut



Options

SCH - Chamfering stylus for insulation

SR - Scoring stylus for peelable semiconductor

Spare part

LMF2 - Spare blade for primary insulation

KIT-MF3/40 - Protective wear pads

BR - Thrust to set the length of insulation to be remove

VBB1 - Screw for locking the thrust

PCR - Quick set up right angled 45° handle

196855 - Straight handle M10

108098 - Clamping knob for blade

LS-C - Spare blade for peelable semiconductor with chamfer

SRC - Scoring stylus for peelable semiconductor with chamfer

Associated tool

ALROC-FENTE - Tool to perform slits on cable's outer sheath

ROTO-TMG - Connector holder for bolted and clamping connections

C-SR - Wrench to replace the semiconductor blade

DSP - Peelable semiconductor lifter

MV cables Tools
MF3/45-C



Part Number	Diameter	Tool capacity			Dimensions			Packaging
		Pelable semicon thickness capacity	Insulation thickness capacity	Stylus included	Length	Width	Height	
MF3/45-C	16 - 45 mm 0,630 - 1,772 in	0,4 - 1,5 mm / 0,016 - 0,040 in	7 mm / 0,276 in	SRC	303 mm 11,929 in	95 mm 3,740 in	165 mm 6,496 in	box