

Certifications

Approved by ENEDIS

Section

MV Shield

Application

Field

Laboratory



PRODUCT BENEFITS

Limited opening angle given by the tool so that the aluminium will not break

TOOL CAPACITY

Diameter	15 - 240 mm 0,591 - 9,449 inch
----------	-----------------------------------

TOOL DIMENSIONS

Length	230 mm
--------	--------

Width	15 mm
-------	-------

Height	40 mm
--------	-------

Weight without box	0,24 Kg
--------------------	---------

Packaging	None
-----------	------

ALROC SAS

Z.I. de la Fonderie - 72160 TUFFE
FRANCE

Phone: +33 2 43 71 11 80

Fax number : +33 2 43 71 16 51

www.alroc.fr

Tool to spread PE outer sheath with aluminium screen

TO DO WHAT

The EV/NPT enables the user to spread the tabs of the PE outer sheath with glued aluminium screen (among them, cable : C33-226 Popy and Nikol), without damaging the aluminium screen and in order to slide in the screen ring



Associated tool

ALROC-FENTE - Tool to perform slits on cable's outer sheath

ROTO-TMG - Connector holder for bolted and clamping connections

K7/GRATT - Cartidge dedicated to sheath abrading, to be mounted on tool ROTO-TMG

GFE-TMG - Roller block for ROTO-TMG to tighten the outer sheath over screen connection

MV cables Tools

EV/NPT



Part Number	Diameter	Tool capacity	Dimensions			Packaging
			Length	Width	Height	
EV/NPT	15 - 240 mm 0,591 - 9,449 in		230 mm 9,055 in	15 mm 0,591 in	40 mm 1,575 in	none