

Section _____

MV Outer sheath

Application _____

Field

Laboratory

**PRODUCT BENEFITS**

Made in bronze aluminium for added durability

TOOL CAPACITY

Diameter	20 - 30 mm 0,787 - 1,181 inch
-----------------	----------------------------------

C33-226 Vinyl / UTE C33-223	50 to 240 mm ²
--	---------------------------

NFC33-223 / HN33S23	50 to 95 mm ²
--------------------------------	--------------------------

TOOL DIMENSIONS

Length	180 mm
---------------	--------

Width	28 mm
--------------	-------

Height	26 mm
---------------	-------

Weight without box	0,17 Kg
---------------------------	---------

Packaging	None
------------------	------

Tool to spread PVC outer sheath with aluminium screen

TO DO WHAT

The EV2000 150-240 enables the user to spread the tabs of the PVC outer sheath with glued aluminium screen (among them : cable C33-226 Vinyl, UTE C33-223, NFC33-223, HN33S23) in order to ease the positioning of the screen ring under the outer sheath

**Associated tool**

ALROC-FENTE - Tool to perform slits on cable's outer sheath

ROTO-TMG - Connector holder for bolted and clamping connections

K7/GRATT - Cartridge dedicated to sheath abrading, to be mounted on tool ROTO-TMG

GFE-TMG - Roller block for ROTO-TMG to tighten the outer sheath over screen connection

ALROC SAS

Z.I. de la Fonderie - 72160 TUFFE
FRANCE

Phone: +33 2 43 71 11 80

Fax number : +33 2 43 71 16 51

www.alroc.fr

MV cables Tools

EV2000 150-240



Part Number	Diameter	Tool capacity		Dimensions			Packaging
		C33-226 Vinyl / UTE C33-223	NFC33-223 / HN33S23	Length	Width	Height	
EV 150/240	25 - 40 mm 0,984 - 1,575 in	-	150 to 240 mm ²	180 mm 7,087 in	32 mm 1,260 in	26 mm 1,024 in	none
EV 630	40 - 60 mm 1,575 - 2,362 in	630 mm ²	630 mm ²	180 mm 7,087 in	36 mm 1,417 in	28 mm 1,102 in	none
EV2000 150-240	20 - 30 mm 0,787 - 1,181 in	50 to 240 mm ²	50 to 95 mm ²	180 mm 7,087 in	28 mm 1,102 in	26 mm 1,024 in	none