

Section _____

HV Outer sheath

Application _____

Field

Laboratory



PRODUCT BENEFITS

Sound alert when the blade is touching the aluminium/lead shield

TOOL CAPACITY

Diameter 50 - 95 mm
1,969 - 3,740 inch

Thickness capacity 7 mm / 0,276 in

Shield detection Yes

TOOL DIMENSIONS

Length 260 mm

Width 160 mm

Height 320 mm

Weight without box 4,1 Kg

Packaging Case

Stripping tool for HV and EHV cable's outer sheath and shield

TO DO WHAT

The DMS 50-95 enables the user to remove the outer sheath and the aluminium/lead shield on HV and EHV cable by successively performing a longitudinal and circular cut



Spare part

LDMS - Spare blade for outer sheath and shield
193725 - 6 volts battery diameter 13x25 mm

Associated tool

EGA - HV and EHV cable's outer sheath and shield spreaders
EV HTB - HV and EHV cable's outer sheath and shield splitters
EVP - HV and EHV cable's lead sheath splitters

ALROC SAS

Z.I. de la Fonderie - 72160 TUFFE

FRANCE

Phone: +33 2 43 71 11 80

Fax number : +33 2 43 71 16 51

www.alroc.fr

HV cables Tools

DMS 50-95



Part Number	Diameter	Tool capacity		Dimensions			Packaging
		Thickness capacity	Shield detection	Length	Width	Height	
DM 50-95	50 - 95 mm 1,969 - 3,740 in	7 mm / 0,276 in	No	260 mm 10,236 in	160 mm 6,299 in	320 mm 12,598 in	case
DM 95-145	95 - 145 mm 3,740 - 5,709 in	11 mm / 0,433 in	No	280 mm 11,024 in	180 mm 7,087 in	360 mm 14,173 in	case
DMS 50-95	50 - 95 mm 1,969 - 3,740 in	7 mm / 0,276 in	Yes	260 mm 10,236 in	160 mm 6,299 in	320 mm 12,598 in	case
DMS 95-145	95 - 145 mm 3,740 - 5,709 in	11 mm / 0,433 in	Yes	280 mm 11,024 in	180 mm 7,087 in	360 mm 14,173 in	case