

## Certifications

Approved by ENEDIS

## Section

LV

## Application

Field



## PRODUCT BENEFITS

Oscillating cable support for a better guidance  
Stripping of sectoral phases of network cable

Longitudinal head with 3 penetrations to adapt to different thickness of sheath  
Interchangeable longitudinal heads for a better versatility

## TOOL CAPACITY

**Diameter** 10 - 30 mm  
0,394 - 1,181 inch

**Circular cutting thickness capacity (mm / inch)** 1,2 mm / 0,047 in

**Longitudinal cutting thickness capacity (mm / inch)** 1,2 - 1,6 - 1,8 mm / 0,047 - 0,063 - 0,070 in

## TOOL DIMENSIONS

**Length** 260 mm

**Width** 90 mm

**Height** 80 mm

**Weight without box** 0,58 Kg

**Packaging** Box

**ALROC SAS**

Z.I. de la Fonderie - 72160 TUFFE  
FRANCE

Phone: +33 2 43 71 11 80

Fax number : +33 2 43 71 16 51

www.alroc.fr

## LV interchangeable 3 penetration pliers for connection cable

### TO DO WHAT

The PINTEL4BT/1216-R removes the outer sheath for power off working  
Cutting depths are adapted to others connection cable  
Circular cutting depth : 1,2 / 1,6 / 1,8 mm / 0,047 / 0,063 / 0,070 in



### Options

TRL - 3 penetrations  
TRL - 1 penetration  
SGM - Large size pouch

### Spare part

MTCP4/12 - Spare blade for circular cutting 1,2 mm / 0,047 in (x3)  
TRL/12-16-18 - Spare interchangeable longitudinal cutting head

### Associated tool

PINTEL4BT/1216 - Stripping pliers for Low-Voltage secondary distribution cable's outer jacket  
PINTEL4BT/1216R1000V - Live line stripping pliers for Low-Voltage sec distribution cable's outer jacket

LV cables Tools

# PINTEL4BT/1216-R



Part Number	Diameter	Tool capacity		Dimensions			Packaging
		Circular cutting thickness capacity (mm / inch)	Longitudinal cutting thickness capacity (mm / inch)	Length	Width	Height	
PINTEL4BT/1216-R	10 - 30 mm 0,394 - 1,181 in	1,2 mm / 0,047 in	1,2 - 1,6 - 1,8 mm / 0,047 - 0,063 - 0,070 in	260 mm 10,236 in	90 mm 3,543 in	80 mm 3,150 in	box