

Certifications

EN 60900:2012

Section

LV Live working

Application

Field



PRODUCT BENEFITS

The frame on which the blade is mounted, acts like a thrust preventing any cut over 4mm / 0,157 in

TOOL CAPACITY

Diameter 10 - 200 mm
0,394 - 7,874 inch

Cutting thickness max 4 mm / 0,157 in

Ø (mm/inch) All

TOOL DIMENSIONS

Length 350 mm

Width 53 mm

Height 53 mm

Weight without box 0,33 Kg

Packaging Box

Insulated strip saw / Live working strip saw (1000V)

TO DO WHAT

The SBI enables the user to cut the strip of armored cable when working on energized cables



Spare part

LSBI - Spare blade

Associated tool

SBA - Aluminium strip saw

PF3/06 - Pliers to remove LC Shield (Longitudinal Corrugated shield)

ALROC SAS

Z.I. de la Fonderie - 72160 TUFFE

FRANCE

Phone: +33 2 43 71 11 80

Fax number : +33 2 43 71 16 51

www.alroc.fr

LV cables Tools

SBI



Part Number	Diameter	Tool capacity		Dimensions			Packaging
		Cutting thickness max	Ø (mm/inch)	Length	Width	Height	
SBI	10 - 200 mm 0,394 - 7,874 in	4 mm / 0,157 in	All	350 mm 13,780 in	53 mm 2,087 in	53 mm 2,087 in	box