

**Certifications**

Approved by ENEDIS

Section

LV

Application

Field

**PRODUCT BENEFITS**

Oscillating cable support for a better guidance
 Stripping of sectoral phases of network cable
 Interchangeable longitudinal heads for a better versatility

TOOL CAPACITY

Diameter 10 - 30 mm
 0,394 - 1,181 inch

Circular cutting thickness capacity (mm / inch) 1,2 mm / 0,047 in

Longitudinal cutting thickness capacity (mm / inch) 1,6 mm / 0,063 in

TOOL DIMENSIONS

Length 260 mm

Width 90 mm

Height 80 mm

Weight without box 0,58 Kg

Packaging Box

ALROC SAS

Z.I. de la Fonderie - 72160 TUFFE
 FRANCE

Phone: +33 2 43 71 11 80

Fax number : +33 2 43 71 16 51

www.alroc.fr

LV pliers for connection cable**TO DO WHAT**

The PINTEL4BT/1216 removes the outer sheath for power off working
 Cutting depths are adapted to others connection cable

**Options**

TRL - 1 penetration

SGM - Large size pouch

Spare part

MTCP4/12 - Spare blade for circular cutting 1,2 mm / 0,047 in (x3)

TRL/17-19-21 - Spare interchangeable longitudinal cutting head

Associated tool

PINTEL4BT/1216 - Stripping pliers for Low-Voltage secondary distribution cable's outer jacket

PINTEL4BT/1216R1000V - Live line stripping pliers for Low-Voltage sec distribution cable's outer jacket

LV cables Tools

PINTEL4BT/1216



Part Number	Diameter	Tool capacity		Dimensions			Packaging
		Circular cutting thickness capacity (mm / inch)	Longitudinal cutting thickness capacity (mm / inch)	Length	Width	Height	
PINTEL4BT/1216	10 - 30 mm 0,394 - 1,181 in	1,2 mm / 0,047 in	1,6 mm / 0,063 in	260 mm 10,236 in	90 mm 3,543 in	80 mm 3,150 in	box