

MV cables Tools

EV/NPT-4F



Certifications

Approved by ENEDIS

Section

MV Shield

Application

Field

Laboratory



PRODUCT BENEFITS

Limited opening angle given by the tool so that the aluminium will not break

TOOL CAPACITY

Diameter 35 - 60 mm
1,378 - 2,362 inch

For section 400mm² to 1200mm²

TOOL DIMENSIONS

Length 230 mm

Width 20 mm

Height 55 mm

Weight without box 0,29 Kg

Packaging None

ALROC SAS

Z.I. de la Fonderie - 72160 TUFFE
FRANCE

Phone: +33 2 43 71 11 80

Fax number : +33 2 43 71 16 51

www.alroc.fr

Tool to spread outer sheath with aluminium screen

TO DO WHAT

The EV/NPT-4F enables the user to spread the tabs of the outer sheath with glued aluminium screen, without damaging the aluminium screen and in order to slide in the screen ring (AKA the cheese grater)



Associated tool

ALROC-FENTE - Tool to perform slits on cable's outer sheath

ROTO-TMG - Connector holder for bolted and clamping connections

K7/GRATT - Cartridge dedicated to sheath abrading, to be mounted on tool ROTO-TMG

GFE-TMG - Roller block for ROTO-TMG to tighten the outer sheath over screen connection

MV cables Tools

EV/NPT-4F



Part Number	Diameter	Tool capacity	Dimensions			Packaging
		For section	Length	Width	Height	
EV/NPT-4F	35 - 60 mm 1,378 - 2,362 in	400mm ² to 1200mm ²	230 mm 9,055 in	20 mm 0,787 in	55 mm 2,165 in	none