

Certifications

Approved by ENEDIS

Section

MV Sets

Application

Field

Laboratory

**PRODUCT BENEFITS**

With spare blades

TOOL CAPACITY

Diameter	16 - 45 mm 0,630 - 1,772 inch
-----------------	----------------------------------

Section according to voltage rating	50 - 400mm ²
--	-------------------------

Pencil tool included	None
-----------------------------	------

TOOL DIMENSIONS

Length	575 mm
---------------	--------

Width	470 mm
--------------	--------

Height	145 mm
---------------	--------

Weight without box	11 Kg
---------------------------	-------

Packaging	Case
------------------	------

Full kit for distribution underground cable 50 mm² up to 400 mm²

TO DO WHAT

Tools included in the kit CNPT/HTA-400-RSM enable the user to splice each layer of distribution underground cable ranging from 50 mm² up to 400 mm² in 12/20 kV, prior to junctions or terminations installation.

For any other voltage rating, please check the outer diameter capacity of each tools included in the kit

**Case**

MF3/45-C - Multifunction tool for outer sheath, peelable semiconductor and insulation

CWB/12-44 - Tool to remove bonded semiconductor with chamfer on the semiconductor cutback

MVS - Stop for tools

SCH - Chamfering stylus for insulation

ALROC-FENTE - Tool to perform slits on cable's outer sheath

ROTO-TMG - Connector holder for bolted and clamping connections

GFE-TMG - Roller block for ROTO-TMG to tighten the outer sheath over screen connection

K7/GRATT - Cartidge dedicated to sheath abrading, to be mounted on tool ROTO-TMG

EV/NPT - Tool to spread PE outer sheath with aluminium screen

EV/NPT-4F - Tool to spread PE outer sheath with aluminium screen

GRI - Scraper for residues of bonded semiconductor

LIGAREX - Clamping tool with return spring for straps

ALROC SAS

Z.I. de la Fonderie - 72160 TUFFE
FRANCE

Phone: +33 2 43 71 11 80

Fax number : +33 2 43 71 16 51

www.alroc.fr

MV cables Tools

CNPT/HTA-400-RSM



Part Number	Diameter	Tool capacity		Dimensions			Packaging
		Section according to voltage rating	Pencil tool included	Length	Width	Height	
CNPT/HTA-400-RSM	16 - 45 mm 0,630 - 1,772 in	50 - 400mm ²	None	575 mm 22,638 in	470 mm 18,504 in	145 mm 5,709 in	case
CNPT/HTA-630-RSM	16 - 58 mm 0,630 - 2,283 in	50 - 630mm ²	None	575 mm 22,638 in	470 mm 18,504 in	145 mm 5,709 in	case