

Certifications

Approved by ENEDIS

Section

MV Sets

Application

Field

Laboratory

**PRODUCT BENEFITS****TOOL CAPACITY**

Diameter	16 - 58 mm 0,630 - 2,283 inch
-----------------	----------------------------------

Section according to voltage rating	35 - 630mm ²
--	-------------------------

Penciling tool included	TC630
--------------------------------	-------

TOOL DIMENSIONS

Length	575 mm
---------------	--------

Width	470 mm
--------------	--------

Height	145 mm
---------------	--------

Weight without box	10 Kg
---------------------------	-------

Packaging	Case
------------------	------

ALROC SASZ.I. de la Fonderie - 72160 TUFFE
FRANCE

Phone: +33 2 43 71 11 80

Fax number : +33 2 43 71 16 51

www.alroc.fr

Full kit for distribution underground cable 35 mm² up to 630 mm² with penciling tool

TO DO WHAT

Tools included in the kit CNPT/630-1-MV-NG enable the user to splice each layer of distribution underground cable ranging from 35 mm² up to 630 mm² in 12/20 kV, prior to junctions or terminations installation.

630mm² Insulation penciling tools included

For any other voltage rating, please check the outer diameter capacity of each tools included in the kit

**Options**

GRI - Scraper for residues of bonded semiconductor

Associated tool

SRC-D - Scoring stylus for peelable semiconductor with chamfer on the transition

CPM-TC223-NG - Additional case 5 TC for NF C33-223 cables

CKM-HTA-630-NG - Case for self service kit for MV 630 NG case

Case

MF2/60 - Multifunction tool for outer sheath and insulation

MF1+/60 - Tool for bonded semiconductor and peelable with stylus

SCH - Chamfering stylus for insulation

ALROC-FENTE - Tool to perform slits on cable's outer sheath

ROTO-TMG - Connector holder for bolted and clamping connections

GFE-TMG - Roller block for ROTO-TMG to tighten the outer sheath over screen connection

K7/GRATT - Cartidge dedicated to sheath abrading, to be mounted on tool ROTO-TMG

EV/NPT - Tool to spread PE outer sheath with aluminium screen

EV 630 - Tool to spread PVC outer sheath with aluminium screen

LIGAREX - Clamping tool with return spring for straps

TC630 - Penciling tool for insulation for 630mm² in 12/20 kV cables

MV cables Tools

CPV-BJ1/35-630



Part Number	Diameter	Tool capacity		Dimensions			Packaging
		Section according to voltage rating	Pencil tool included	Length	Width	Height	
CPV-BJ1/35-630	16 - 58 mm 0,630 - 2,283 in	35 - 630mm ²	TC630	575 mm 22,638 in	470 mm 18,504 in	145 mm 5,709 in	case