

Section _____

MV Outer sheath

Application _____

Field

Laboratory

**PRODUCT BENEFITS**

Made in bronze aluminium for added durability

TOOL CAPACITY

Diameter 25 - 40 mm
0,984 - 1,575 inch

C33-226 Vinyl /
UTE C33-223

NFC33-223 /
HN33S23 150 to 240 mm²

TOOL DIMENSIONS

Length 180 mm

Width 32 mm

Height 26 mm

Weight without box 0,18 Kg

Packaging None

Tool to spread PVC outer sheath with aluminium screen

TO DO WHAT

The EV 150/240 enables the user to spread the tabs of the PVC outer sheath with glued aluminium screen (among them : cable NFC33-223, HN33S23) in order to ease the positioning of the screen ring under the outer sheath

**Associated tool**

ALROC-FENTE - Tool to perform slits on cable's outer sheath

ROTO-TMG - Connector holder for bolted and clamping connections

K7/GRATT - Cartidge dedicated to sheath abrading, to be mounted on tool ROTO-TMG

GFE-TMG - Roller block for ROTO-TMG to tighten the outer sheath over screen connection

ALROC SAS

Z.I. de la Fonderie - 72160 TUFFE
FRANCE

Phone: +33 2 43 71 11 80

Fax number : +33 2 43 71 16 51

www.alroc.fr

MV cables Tools

EV 150/240



Part Number	Diameter	Tool capacity		Dimensions			Packaging
		C33-226 Vinyl / UTE C33-223	NFC33-223 / HN33S23	Length	Width	Height	
EV 150/240	25 - 40 mm 0,984 - 1,575 in	-	150 to 240 mm ²	180 mm 7,087 in	32 mm 1,260 in	26 mm 1,024 in	none
EV 630	40 - 60 mm 1,575 - 2,362 in	630 mm ²	630 mm ²	180 mm 7,087 in	36 mm 1,417 in	28 mm 1,102 in	none
EV2000 150-240	20 - 30 mm 0,787 - 1,181 in	50 to 240 mm ²	50 to 95 mm ²	180 mm 7,087 in	28 mm 1,102 in	26 mm 1,024 in	none