

**Section**

MV Outer sheath

**Application**Field  
Laboratory  
Production**PRODUCT BENEFITS**Quick set up  
Fits on PR4, PRG3 and PRG4**TOOL CAPACITY**

<b>Diameter</b>	10 - 75 mm 0,394 - 2,953 inch
-----------------	----------------------------------

<b>Thickness capacity</b>	4,0 mm / 0,157 in
---------------------------	-------------------

**TOOL DIMENSIONS**

<b>Length</b>	50 mm
---------------	-------

<b>Width</b>	40 mm
--------------	-------

<b>Height</b>	40 mm
---------------	-------

<b>Weight without box</b>	0,04 Kg
---------------------------	---------

<b>Packaging</b>	None
------------------	------

**ALROC SAS**Z.I. de la Fonderie - 72160 TUFFE  
FRANCE

Phone: +33 2 43 71 11 80

Fax number : +33 2 43 71 16 51

www.alroc.fr

## Interchangeable longitudinal cutting head with one cutting depth

**TO DO WHAT**

The TRL with single cutting depth, fits on any PR4, PRG3, PRG4 pliers in order to change the longitudinal cutting depth of the pliers according to the thickness of the outer sheath of the cable

Any cutting depth is available from 0,5 mm/ 0,019 in up to 5 mm/ 0,196 inch

How does the P/N works : TRL/\*\*

\*\*= Cutting depth (e.g : TRL/25 -> cutting depth 2.5 mm)

**Associated tool**

PRG3/C21-L212528 - Pliers for outer sheath for cable with O.D from Ø26mm/1,024in up to 52mm/2,047in

-

-

# MV cables Tools

## TRL/40



Part Number	Diameter	Tool capacity	Dimensions			Packaging
		Thickness capacity	Length	Width	Height	
TRL/12	10 - 75 mm 0,394 - 2,953 in	1,2 mm / 0,047 in	50 mm 1,969 in	40 mm 1,575 in	40 mm 1,575 in	none
TRL/15	10 - 75 mm 0,394 - 2,953 in	1,5 mm / 0,059 in	50 mm 1,969 in	40 mm 1,575 in	40 mm 1,575 in	none
TRL/18	10 - 75 mm 0,394 - 2,953 in	1,8 mm / 0,070 in	50 mm 1,969 in	40 mm 1,575 in	40 mm 1,575 in	none
TRL/20	10 - 75 mm 0,394 - 2,953 in	2,0 mm / 0,078 in	50 mm 1,969 in	40 mm 1,575 in	40 mm 1,575 in	none
TRL/25	10 - 75 mm 0,394 - 2,953 in	2,5 mm / 0,098 in	50 mm 1,969 in	40 mm 1,575 in	40 mm 1,575 in	none
TRL/30	10 - 75 mm 0,394 - 2,953 in	3,0 mm / 0,118 in	50 mm 1,969 in	40 mm 1,575 in	40 mm 1,575 in	none
TRL/35	10 - 75 mm 0,394 - 2,953 in	3,5 mm / 0,138 in	50 mm 1,969 in	40 mm 1,575 in	40 mm 1,575 in	none
TRL/40	10 - 75 mm 0,394 - 2,953 in	4,0 mm / 0,157 in	50 mm 1,969 in	40 mm 1,575 in	40 mm 1,575 in	none
TRL/45	10 - 75 mm 0,394 - 2,953 in	4,5 mm / 0,177 in	50 mm 1,969 in	40 mm 1,575 in	40 mm 1,575 in	none
TRL/50	10 - 75 mm 0,394 - 2,953 in	5,0 mm / 0,196 in	50 mm 1,969 in	40 mm 1,575 in	40 mm 1,575 in	none