

## Section

MV Outer sheath

## Application

Field  
Laboratory  
Production



## PRODUCT BENEFITS

Quick set up on the plieers  
Quick switch from one cutting  
depth to another  
Fits on PR4, PRG3 and PRG4

## TOOL CAPACITY

Diameter	10 - 75 mm 0,394 - 2,953 inch
Thickness capacity	1,0-1,5-2,0 mm / 0,039-0,059-0,078 in

## TOOL DIMENSIONS

Length	60 mm
Width	40 mm
Height	40 mm
Weight without box	0,07 Kg
Packaging	None

## ALROC SAS

Z.I. de la Fonderie - 72160 TUFFE  
FRANCE

Phone: +33 2 43 71 11 80

Fax number : +33 2 43 71 16 51

www.alroc.fr

## Interchangeable longitudinal cutting head with three cutting depths

## TO DO WHAT

The TRL with three cutting depth, fits on any PR4, PRG3, PRG4 pliers in order to change the longitudinal cutting depth of the pliers according to the thickness of the outer sheath of the cable

This TRL has three cutting depth easily identifiable thanks to the markings located on the protective casing of the cutting head

Any cutting depth is available from 0,5 mm / 0,019 in up to 5 mm / 0,196 in

How does the P/N works : TRL/\*\*-\*\*-\*\*

\*\*-\*\*-\*\*= Cutting depth (e.g : TRL/24-28-32 -> cutting depth 2.4, 2.8 and 3.2 mm)



## Associated tool

PRG3/C21-L212528 - Pliers for outer sheath for cable with O.D from Ø26mm/1,024in up to 52mm/2,047in

-  
-



Part Number	Diameter	Tool capacity	Dimensions			Packaging
		Thickness capacity	Length	Width	Height	
TRL/10-12-14	10 - 75 mm 0,394 - 2,953 in	1,0-1,2-1,4 mm / 0,039-0,047-0,055 in	60 mm 2,362 in	40 mm 1,575 in	40 mm 1,575 in	none
TRL/10-12-16	10 - 75 mm 0,394 - 2,953 in	1,0-1,2-1,4 mm / 0,039-0,047-0,055 in	60 mm 2,362 in	40 mm 1,575 in	40 mm 1,575 in	none
TRL/10-15-20	10 - 75 mm 0,394 - 2,953 in	1,0-1,5-2,0 mm / 0,039-0,059-0,078 in	60 mm 2,362 in	40 mm 1,575 in	40 mm 1,575 in	none
TRL/12-16-18	10 - 75 mm 0,394 - 2,953 in	1,2-1,6-1,8 mm / 0,047-0,062-0,070 in	60 mm 2,362 in	40 mm 1,575 in	40 mm 1,575 in	none
TRL/16-18-20	10 - 75 mm 0,394 - 2,953 in	1,6-1,8-2,0 mm / 0,062-0,070-0,078 in	60 mm 2,362 in	40 mm 1,575 in	40 mm 1,575 in	none
TRL/20-24-28	10 - 75 mm 0,394 - 2,953 in	2,0-2,4-2,8 mm / 0,078-0,094-0,110 in	60 mm 2,362 in	40 mm 1,575 in	40 mm 1,575 in	none
TRL/22-28-33	10 - 75 mm 0,394 - 2,953 in	2,2-2,8-3,3 mm / 0,086-0,110-0,129 in	60 mm 2,362 in	40 mm 1,575 in	40 mm 1,575 in	none
TRL/24-28-32	10 - 75 mm 0,394 - 2,953 in	2.4 / 2.8 / 3.2 mm	60 mm 2,362 in	40 mm 1,575 in	40 mm 1,575 in	none
TRL/26-32-38	10 - 75 mm 0,394 - 2,953 in	2,6-3,2-3,8 mm / 0,102-0,126-1,150 in	60 mm 2,362 in	40 mm 1,575 in	40 mm 1,575 in	none