

## Section

MV Outer sheath

## Application

Field  
Laboratory  
Production

## PRODUCT BENEFITS

Quick set up on the plieers  
Quick switch from one cutting  
depth to another  
Fits on PR4, PRG3 and PRG4

## TOOL CAPACITY

**Diameter** 10 - 75 mm  
0,394 - 2,953 inch

**Thickness  
capacity** 2,6-3,2-3,8 mm /  
0,102-0,126-1,150 in

## TOOL DIMENSIONS

**Length** 60 mm

**Width** 40 mm

**Height** 40 mm

**Weight without box** 0,07 Kg

**Packaging** None

## ALROC SAS

Z.I. de la Fonderie - 72160 TUFFE  
FRANCE

Phone: +33 2 43 71 11 80

Fax number : +33 2 43 71 16 51

www.alroc.fr

## Interchangeable longitudinal cutting head with three cutting depths

## TO DO WHAT

The TRL with three cutting depth, fits on any PR4, PRG3, PRG4 pliers in order to change the longitudinal cutting depth of the pliers according to the thickness of the outer sheath of the cable

This TRL has three cutting depth easily identifiable thanks to the markings located on the protective casing of the cutting head

Any cutting depth is available from 0,5 mm/ 0,019 in up to 3,8 mm/ 0,196 in

How does the P/N works : TRL/\*\*-\*\*-\*\*

\*\*\_\*\*-\*\*= Cutting depth (e.g : TRL/24-28-32 -> cutting depth 2,4 - 2,8 and 3,2 mm / 0,094 - 0,110 and 0,126 in)



## Associated tool

PRG3/C21-L212528 - Pliers for outer sheath for cable with O.D from Ø26mm/1,024in up to 52mm/2,047in



| Part Number         | Diameter                       | Tool capacity                         | Dimensions        |                   |                   | Packaging |
|---------------------|--------------------------------|---------------------------------------|-------------------|-------------------|-------------------|-----------|
|                     |                                | Thickness capacity                    | Length            | Width             | Height            |           |
| TRL/10-12-14        | 10 - 75 mm<br>0,394 - 2,953 in | 1,0-1,2-1,4 mm / 0,039-0,047-0,055 in | 60 mm<br>2,362 in | 40 mm<br>1,575 in | 40 mm<br>1,575 in | none      |
| TRL/10-12-16        | 10 - 75 mm<br>0,394 - 2,953 in | 1,0-1,2-1,4 mm / 0,039-0,047-0,055 in | 60 mm<br>2,362 in | 40 mm<br>1,575 in | 40 mm<br>1,575 in | none      |
| TRL/10-15-20        | 10 - 75 mm<br>0,394 - 2,953 in | 1,0-1,5-2,0 mm / 0,039-0,059-0,078 in | 60 mm<br>2,362 in | 40 mm<br>1,575 in | 40 mm<br>1,575 in | none      |
| TRL/12-16-18        | 10 - 75 mm<br>0,394 - 2,953 in | 1,2-1,6-1,8 mm / 0,047-0,062-0,070 in | 60 mm<br>2,362 in | 40 mm<br>1,575 in | 40 mm<br>1,575 in | none      |
| TRL/16-18-20        | 10 - 75 mm<br>0,394 - 2,953 in | 1,6-1,8-2,0 mm / 0,062-0,070-0,078 in | 60 mm<br>2,362 in | 40 mm<br>1,575 in | 40 mm<br>1,575 in | none      |
| TRL/20-24-28        | 10 - 75 mm<br>0,394 - 2,953 in | 2,0-2,4-2,8 mm / 0,078-0,094-0,110 in | 60 mm<br>2,362 in | 40 mm<br>1,575 in | 40 mm<br>1,575 in | none      |
| TRL/22-28-33        | 10 - 75 mm<br>0,394 - 2,953 in | 2,2-2,8-3,3 mm / 0,086-0,110-0,129 in | 60 mm<br>2,362 in | 40 mm<br>1,575 in | 40 mm<br>1,575 in | none      |
| TRL/24-28-32        | 10 - 75 mm<br>0,394 - 2,953 in | 2.4 / 2.8 / 3.2 mm                    | 60 mm<br>2,362 in | 40 mm<br>1,575 in | 40 mm<br>1,575 in | none      |
| <b>TRL/26-32-38</b> | 10 - 75 mm<br>0,394 - 2,953 in | 2,6-3,2-3,8 mm / 0,102-0,126-1,150 in | 60 mm<br>2,362 in | 40 mm<br>1,575 in | 40 mm<br>1,575 in | none      |